



ISO9001 Certified supplier



FREEFLO FH Housings

Freeflo FH multicartridge filter housings

The FH series of filter housings are free standing multicartridge housings made from 304 stainless steel. They are intended as a mid range option suitable for flows from 4 – 15,000L/hr. The housings are available in three sizes, 4 x 20", 4 x 40" or 4 x 50".

The FH series accept any standard double open ended cartridge, they are not suitable for o-ring seal cartridges. Cartridge changing is quick and simple with positive location using cartridge guide rods and an internal top seal plate.

- ❖ 304L stainless steel construction, 316L internal parts. All 316L optional.
- ❖ Compatible with most chemical sterilants, hot water and steam.
- ❖ 50mm female threaded connections (15mm drain).
- ❖ Optional Triclamp sanitary connections
- ❖ Cartridge micron ratings from 0.02 to 200.
- ❖ Bolt down holes in base.
- ❖ 20" or 40" versions available.
- ❖ For water or other liquids.
- ❖ Made in the USA.

Specifications

Operating conditions:

Pressure: 150 psi (1000kPa)
Temp: Cartridge dependent (up to 120°C)



Dimensions/typical flows

MODEL	CARTRIDGES	FLOW ⁽¹⁾ L/hr	HEIGHT (mm)	WEIGHT (kg)
FH8	4 x 20"	5,000	750	14
FH16	4 x 40"	10,000	1250	20
FH20	5 x 40"	12,500	1250	21

1) Recommended maximum flow for continuous operation with 1 micron depth cartridge.



PO Box 14-641
Auckland 6
Tel: 09 570 9135
Fax 09 527 7654
www.contam.co.nz